

# MATERIAL SAFETY DATA SHEET

## 7821

### I. PRODUCT AND COMPANY IDENTIFICATION

<b>PRODUCT NAME:</b>	URETHANE CO-REACTANT
<b>PRODUCT CODE:</b>	7821
<b>DOCUMENT ID:</b>	M7821
<b>COMPANY:</b>	NEOGARD® - a Division of JONES-BLAIR® Company 2728 Empire Central Dallas, TX 75235 1-214-353-1600
<b>REVISION NUMBER:</b>	2
<b>PRIOR VERSION DATE:</b>	01-03-2008
<b>CHEMICAL FAMILY:</b>	Urethane Co-Reactant
<b>INTENDED USE:</b>	Urethane Paint Hardener/Catalyst
<b>EMERGENCY CONTACT:</b>	ChemTrec Center
<b>EMERGENCY PHONE:</b>	1-800-424-9300

### II. HAZARDS IDENTIFICATION

<b>EMERGENCY OVERVIEW:</b>	<b>DANGER!</b> Causes skin irritation. Causes eye irritation. Causes nose and throat irritation. Vapor and spray mist harmful. Causes nose and throat irritation. Overexposure may cause lung damage. May cause allergic skin and respiratory reaction. Effects may be permanent.
----------------------------	---

**AL-KOAT**<sup>MR</sup>  
IMPERMEABILIZANTES

by



# MATERIAL SAFETY DATA SHEET

<b>TARGET ORGANS POTENTIALLY AFFECTED BY EXPOSURE:</b>	<ul style="list-style-type: none"><li>• Respiratory Tract</li><li>• Skin</li></ul>
<b>MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:</b>	<ul style="list-style-type: none"><li>• Skin allergies.</li><li>• Individuals with lung or breathing problems or prior reaction to isocyanates must not be exposed to vapor or spray mist.</li></ul>

## IMMEDIATE (ACUTE) HEALTH EFFECTS BY ROUTE OF EXPOSURE:

<b>SKIN CONTACT:</b>	Sensitizer. Avoid exposure. If sensitized, repeated exposures will result in irritation, reddening, and rashes even for very low exposures.
----------------------	---

## LONG-TERM (CHRONIC) HEALTH EFFECTS:

<b>INHALATION:</b>	<p>Isocyanate vapors or mist at concentrations above the TLV can irritate the mucous membranes in the respiratory tract causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function. Exposure well above the TLV may lead to generally reversible bronchitis, bronchial spasm and pulmonary edema.</p> <p>Repeated overexposure causes sensitization in some individuals resulting in asthma-like symptoms on subsequent exposures below the TLV.</p> <p>Persons with preexisting bronchial hyperactivity can respond to concentrations below the TLV with similar symptoms as well as an asthma attack.</p>
<b>SKIN CONTACT:</b>	Prolonged contact may cause an allergic skin reaction.

## III. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	%	CAS #
4,4'-DIPHENYLMETHANE DIISOCYANATE	50 - 70	101-68-8
MDI Homopolymer	15 - 40	39310-05-9

# MATERIAL SAFETY DATA SHEET

## IV. FIRST-AID MEASURES

<b>INHALATION:</b>	If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If breathing difficulty persists or occurs later, consult a physician and have MSDS available.
<b>EYES:</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
<b>SKIN CONTACT:</b>	Wash with soap and water. Get medical attention if irritation develops or persists.
<b>INGESTION:</b>	If swallowed, do not induce vomiting. Get medical attention immediately.

## V. FIRE FIGHTING MEASURES

<b>EXTINGUISHING MEDIA:</b>	Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
<b>FIRE AND/OR EXPLOSION HAZARDS:</b>	Not applicable
<b>FIRE FIGHTING METHODS AND PROTECTION:</b>	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment.
<b>HAZARDOUS COMBUSTION PRODUCTS:</b>	Hydrogen cyanide, Carbon dioxide, Carbon monoxide, Nitrogen containing gases, Isocyanates, Isocyanic Acid
<b>FLASH POINT ( F / C):</b>	350 / 177
<b>Autoignition Temperature (°F/°C):</b>	464.0 / 240.0

## VI. ACCIDENTAL RELEASE MEASURES

<b>PERSONAL PRECAUTIONS AND EQUIPMENT:</b>	Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. See MSDS sections III, XIII and XV for disposal
--	---

# MATERIAL SAFETY DATA SHEET

	considerations.
<b>METHODS FOR CLEAN-UP:</b>	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal.

## VII. HANDLING AND STORAGE

<b>HANDLING TECHNICAL MEASURES AND PRECAUTIONS:</b>	Overexposure may be harmful. As with all chemicals, good industrial hygiene practices should be followed when handling this material.
<b>STORAGE TECHNICAL MEASURES AND CONDITIONS:</b>	Store in a cool dry place. Keep container(s) closed.

## VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>ENGINEERING MEASURES:</b>	Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure.
<b>RESPIRATORY PROTECTION:</b>	General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use. For poorly ventilated areas or during spray application use NIOSH approved supplied air respirator unless air monitoring demonstrates vapor/mist levels below applicable limits. When monomeric isocyanate concentrations are below 0.05 ppm (10 times the 8 hour TWA exposure limit), an appropriate combination organic vapor and particulate respirator (NIOSH approved) may be appropriate. An end-of-service-life Indicator (ESLI) or a change schedule is mandatory.
<b>EYE PROTECTION:</b>	Wear chemically resistant safety glasses with side shields when handling this product.
<b>SKIN PROTECTION:</b>	Avoid all skin contact by covering as much of the exposed skin area as possible with appropriate clothing to prevent skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact. Wear chemical resistant gloves.

# MATERIAL SAFETY DATA SHEET

## CONTROL PARAMETERS:

Chemical Name	ACGIH TLV-TWA	ACGIH STEL	OSHA Exposure Limits
4,4'-DIPHENYLMETHANE DIISOCYANATE	0.005 ppm TWA		Not applicable 0.2ppm, 0.2 mg/m
MDI Homopolymer	Not applicable		Not applicable

## IX. PHYSICAL AND CHEMICAL PROPERTIES

**Color:** Colorless to pale yellow  
**Physical State:** Liquid  
**Vapor Density:** ~ 8.5 (air = 1)  
**VOC (g/l)** (Regulatory, Calculated): 0  
(Actual, Calculated): 0  
**Solubility in Water:** Reacts slowly with water.  
**Octanol/Water Partition Coefficient:** Not Available  
**Volatiles, % by Volume** (Calculated): 0.00  
**Volatiles, % by weight** (Calculated): 0.00  
**Wt/Gal:** 9.9 - 10.1

Physical and Chemical Properties are calculated target or range values for single packaged items and do not represent compliance values for multi-component (mixed) systems.

## X. STABILITY AND REACTIVITY

<b>STABILITY:</b>	Stable under normal conditions.
<b>CONDITIONS TO AVOID:</b>	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.
<b>MATERIALS TO AVOID/CHEMICAL INCOMPATIBILITY:</b>	Water, Alcohols, Amines, Acids, Caustics (bases, alkalis)

# MATERIAL SAFETY DATA SHEET

POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Hydrogen cyanide, Carbon dioxide, Carbon monoxide, Nitrogen containing gases, Isocyanates, Isocyanic Acid

## XI. TOXICOLOGICAL INFORMATION

Component Toxicology Data:				
Chemical Name	CAS Number	LD50/LC50		
4,4'-DIPHENYLMETHANE DIISOCYANATE	101-68-8			
MDI Homopolymer	39310-05-9	Inhalation LC50 (2h) Rat 369 mg/m Oral LD50 Rat > 5000 mg/kg Dermal LD50 Rabbit > 5000 mg/kg		
Carcinogens:				
Chemical Name	CAS Number	IARC	NTP	OSHA
Not applicable				

## XII. ECOLOGICAL INFORMATION

Toxicity data, if available, are listed below.
--

# MATERIAL SAFETY DATA SHEET

## XIII. DISPOSAL CONSIDERATIONS

<b>DISPOSAL METHODS:</b>	Refer to other sections of this MSDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.
--------------------------	--

## XIV. TRANSPORTATION INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.	
<b>DOT BASIC DESCRIPTION:</b>	Paint Related Material, Not-Regulated

## XV. REGULATORY INFORMATION

<b>United States Federal Regulations:</b>		
<b>TSCA Status</b> All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.		
<b>SARA EHS Chemicals</b> Furan Propylene oxide	<b>CAS #</b> 110-00-9 75-56-9	<b>%</b> < 10 ppm < 0.1 ppm
<b>CERCLA</b> Methylene diisocyanate	101-68-8	50 - 70
<b>SARA 313</b> Methylenebis(phenylisocyanate) (MDI)	101-68-8	50 - 70
<b>SARA 311/312</b>  Health (Acute): Y Health (chronic): Y Fire (Flammable):N Pressure: N Reactivity: N		
<b>U. S. State Regulations:</b> <b>California Prop 65 Chemicals</b> <b>Cancer</b> Furan	110-00-9 75-07-0	< 10 ppm < 1 ppm

# MATERIAL SAFETY DATA SHEET

Acetaldehyde <b>Reproductive</b> Not applicable		
<b>Canadian Regulations:</b> <b>CEPA DSL:</b> The components of this product ARE listed on the Canadian Domestic Substances List. <b>WHMIS Hazard Class:</b> D2A		

## XVI. ADDITIONAL INFORMATION

<b>PREPARED BY:</b>	Regulatory Department
<b>DISCLAIMER:</b>	This MSDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.
<b>PRINT DATE:</b>	May 28, 2009